



Site 41, Knowsthorpe Way,
Cross Green Industrial Estate, Leeds, LS9 0SW
Telephone: +44 (0) 113 240 3456 Sales: +44 (0) 113 240 2424

Fax: +44 (0) 113 240 0024 e-mail: info@everbuild.co.uk website: www.everbuild.co.uk

# CONSTRUCTION PRODUCTS REGULATION DECLARATION OF PERFORMANCE

No: 825/1-CPR/ 2014

Substrate: Mortar M2

Primer: No primer

1. Identification Code	Everbuild 825 Silicone Sealant;
	Codes: 825 / FP825
2. Type, Batch and/or Serial Number	- For batch number - see packaging
3. Intended use	Sealant for non-structural use in joints in buildings and pedestrian walkways Part 1: Sealants for Façade elements
4. Manufacturer	Everbuild Building Products ltd, Site 41, Cross Green Industrial Estate, Knowsthorpe Way, Leeds, LS9 0SW
5. Authorised Representative	Not Applicable
6. Assessment and Verification of Constancy	System 3
of Performance	
7. Notified Body and Tasks	Ginger CEBTP Notified Body No. 00074
8. European Technical Assessment	Not Applicable
9. Declared Performance	TO EN15651-1 (2012)
Туре	F EXT-INT-CC
Classification	F25LM
Reaction to Fire	Class E



Site 41, Knowsthorpe Way, Cross Green Industrial Estate, Leeds, LS9 0SW Telephone: +44 (0) 113 240 3456 Sales: +44 (0) 113 240 2424

> Fax: +44 (0) 113 240 0024 e-mail: info@everbuild.co.uk website: www.everbuild.co.uk

	Website: WWW.everballa.co.ak
Loss of Volume ISO10563	≤10%
Resistance to flow ISO7390	≤3 mm
Adhesion/cohesion properties at maintained extension after water immersion (23°C) ISO 10590	NF
Adhesion/cohesion properties (-30°C)	≤0.9 MPa
Durability ISO 8340, ISO 9047 and ISO 10590	Pass

Substrate: Glass

Primer: No primer

1. Identification Code	Everbuild 825 Silicone Sealant;
	Codes:
2. Type, Batch and/or Serial Number	- For batch number - see packaging
3. Intended use	Sealant for non-structural use in joints in buildings and pedestrian walkways Part 2: Sealants for Glazing elements
4. Manufacturer	Everbuild Building Products Itd, Site 41, Cross Green Industrial Estate, Knowsthorpe Way, Leeds, LS9 0SW
5. Authorised Representative	Not Applicable
6. Assessment and Verification of Constancy of Performance	System 3
7. Notified Body and Tasks	Ginger CEBTP Notified Body No. 00074
8. European Technical Assessment	Not Applicable
9. Declared Performance	TO EN15651-2 (2012)



Site 41, Knowsthorpe Way, Cross Green Industrial Estate, Leeds, LS9 0SW Telephone: +44 (0) 113 240 3456 Sales: +44 (0) 113 240 2424

> Fax: +44 (0) 113 240 0024 e-mail: info@everbuild.co.uk website: www.everbuild.co.uk

	website. www.everbuild.co.uk
Туре	G-CC
Classification	G25LM
Reaction to Fire	Class E
Loss of Volume ISO10563	≤10%
Resistance to flow ISO7390	≤3 mm
Adhesion/cohesion properties at maintained extension after water immersion (23°C) ISO	NF
10590	
Adhesion/cohesion properties after exposure to heat, water and artificial light ISO 11431	NF
Elastic recovery ISO 7389	≥60%
Adhesion/cohesion properties (-30°C) ISO 8339 modified	≤0.9 MPa
Adhesion/cohesion properties at maintained extension (-30°C) ISO 8340	NF
Durability ISO 8340, ISO 9047 and ISO 10590	Pass

Substrate: Anodised aluminium

Primer: Silicone Primer NP2

1. Identification Code	Everbuild 825 Silicone Sealant;
	Codes:
2. Type, Batch and/or Serial Number	- For batch number - see packaging
3. Intended use	Sealant for non-structural use in joints in buildings and pedestrian walkways Part 3: Sealants for Sanitary elements



Site 41, Knowsthorpe Way,
Cross Green Industrial Estate, Leeds, LS9 0SW
Telephone: +44 (0) 113 240 3456 Sales: +44 (0) 113 240 2424

Fax: +44 (0) 113 240 0024 e-mail: info@everbuild.co.uk website: www.everbuild.co.uk

	website: www.everbuild.co.uk
4. Manufacturer	Everbuild Building Products Itd, Site 41, Cross Green
	Industrial Estate, Knowsthorpe Way, Leeds, LS9 0SW
5. Authorised Representative	Not Applicable
6. Assessment and Verification of Constancy	System 3
of Performance	
7. Notified Body and Tasks	Ginger CEBTP Notified Body No. 00074
8. European Technical Assessment	Not Applicable
9. Declared Performance	TO EN15651-3 (2012)
Туре	S
Classification	XS2
Reaction to Fire	Class E
Loss of Volume ISO10563	≤20%
Resistance to flow ISO7390	≤3 mm
Adhesion/cohesion properties at maintained	NF
extension after water immersion (23°C) ISO	
10590	
Action of the microorganisms : Intensity of	2
growth ISO 846, method B	
Durability ISO 846, method B, ISO 8340, ISO	Pass
9047 and ISO 10590	
-	

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. The declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.



Site 41, Knowsthorpe Way,

Cross Green Industrial Estate, Leeds, LS9 0SW

Telephone: +44 (0) 113 240 3456 Sales: +44 (0) 113 240 2424

Fax: +44 (0) 113 240 0024 e-mail: info@everbuild.co.uk

website: www.everbuild.co.uk

Signed: I. G. Southerington – Head of Technical

P.R. Thomas – Technical Manager

Dated: Leeds, 24/2/14