


# ARBOTHANE 1245

## DESCRIPTION

Arbothane 1245 is a one part Polyurethane Sealant which cures on exposure to moisture vapour to form a tough but flexible rubber. Arbothane 1245 has good adhesion to concrete, brickwork, metals and many other common construction substrates.

## MAIN APPLICATIONS



Recommended for use in floor joints, expansion joints and structural cladding applications.

**NB:** Not recommended for use against natural stone.

## SPECIFICATION COMPLIANCE

BS EN ISO 11600 – F – 25 HM

## APPLICATION INSTRUCTIONS

### Joint Preparation

The joint surfaces must be clean, dry and free from all contamination. The surfaces should be degreased using the appropriate Arbo Cleaner. Primers may be required on some substrates. It is recommended that Adshead Ratcliffe Technical Services Department should be consulted and advice obtained with regard to the choice of primer for specific purposes.

### Joint Backing

Where applicable, appropriate joint filler e.g. closed cell polyethylene foam, should be used to provide the correct joint depth.

### Application

All joint preparation, priming, and sealant application should be carried out in accordance with BS 8000 Part 16, the British Standard for the sealing of joints in buildings using sealants.

Arbothane 1245 is supplied in 600ml foil packs and can be applied into the joint using an Arbo Foil Pack Gun

## JOINT SIZE SUITABILITY

### Joint Width

Minimum 6mm  
Maximum 25mm (single application); for advice on multiple applications please contact Adshead Ratcliffe Technical Services Department.

### Joint Depth

Minimum 10mm on porous substrates  
Minimum 6mm on non-porous substrates  
Maximum 20mm

### Width: Depth ratio (within above min/max restrictions)

2:1 butt joints  
1:1 lap joints

## PACKAGING

20 x 600ml Foils per box. Polyethylene Nozzles are included in each box.

## COLOURS

Grey.

## STORAGE LIFE

12 months in original unopened packaging stored in a cool, dry place out of direct sunlight.

## HEALTH AND SAFETY

Contains isocyanates. Please consult Material Safety Data Sheet for full information.

## TECHNICAL DATA

|                             |  |
|-----------------------------|--|
| Skin Time at 20° C/65 % RH: | 90 minutes   |
| Application Temperature:    | + 5° C to + 40° C  |
| Service Temperature:        | - 30° C to + 110°C   |
| Typical Shore Hardness:     | 45   |
| Cure Rate at 20° C/65 % RH: | 2mm/24 hours   |
| Chemical Resistance:        | Moderate resistance to most dilute acids and alkalis. Organic solvents may cause the sealant to swell and lose adhesion. |
| UV Resistance:              | Very Good  |
| Service Life:               | 15 years+  |
| Movement Accommodation:     | Butt joints (movement in tension and compression): 35 %.   |
|                             | Lap joints (movement in shear): 70 %.  |

**ACCESSORIES****Primers**

Arbokol AG2 Porous Primer (500ml tin). Yield approximately 125 metres per tin

Arbo Primer 7750 (500ml tin). Yield approximately 200 metres per tin

**Cleaners**

Arbo Cleaner No.17- 1 Litre Tin (Xylene based – not suitable for use with plastics or delicate finishes)

Arbo Cleaner No. 16 - 1 Litre Tin (Alcohol Based)

**Ancillary Equipment**

Arbo Foil Pack Gun

**QUANTITY ESTIMATOR**

| <b>Joint Size (mm)</b> | <b>Metres/Litre</b> |
|------------------------|---------------------|
| 6 x 6                  | 27.8                |
| 9 x 6                  | 18.5                |
| 12 x 9                 | 9.3                 |
| 18 x 10                | 5.6                 |
| 25 x 10                | 4.0                 |

**Important:** The information in this leaflet is given in good faith and based on results gained from experience and tests. However, all recommendations or suggestions are made without guarantee since the conditions of use are beyond our control. Goods are supplied subject to the Company's terms and conditions of sales, a copy of which is available on request.

**Arbo sealants are manufactured in the U.K. by Adshead Ratcliffe.**