

CM STAY WHITE **BATH & KITCHEN**

Containing MICROTEC™

TECHNICAL DATA SHEET

March 2015

DESCRIPTION

CM STAY WHITE is a single component silicone sealant which when exposed to atmospheric humidity cures rapidly to form a permanent flexible and extremely durable weather tight sealant. The cured sealant has a good movement accommodation factor throughout a wide temperature range, resistance to mould and bacterial growth.

MICROTEC Silver nano antibacterial technology
a powerful additive which prevents black mould ,mildew and bacterial growth.

CM STAY WHITE bonds strongly to clean uncoated glass, ceramic or painted surfaces without the need for a primer. For most other substrates it is recommended that CM Multi wipes be used to ensure optimal bonding.

CM STAY WHITE should be used on applications where joint loads are high and where relative movement between substrates is minimal.

Packaged in a recyclable grade 310ml cartridge it is ready for immediate use after cleaning surfaces with CM Multi wipes

CM STAY WHITE meets the requirements to BS5889 {Type B} and US Fed Spec TTS 001543A (Class A) and TTS 00230C (Class A) and ISO 11600-F&G-25HM 846

TYPICAL USES

Typical uses of **CM STAY WHITE** are:
Bath and shower jointing kitchen areas,
laboratories, high hygiene areas and construction joints.
For any technical queries contact:
CM SEALANTS TECHNICAL LINE: 020 8519 6358

TECHNICAL SPECIFICATION

Chemical basis:	High modulus single component silicone sealant.
Movement:	Up to a total of +/- 35%
Slump:	Nil
Touch dry:	CM STAY WHITE is touch dry after 30 minutes at 20°C lower temperatures retard curing time.
Through cure time:	10mm in the first seven days at ambient temperature of 20°C
Application temperature:	Do not apply CM STAY WHITE at temperatures below 5°C or above 40°C
Service Temperature:	In normal use -50°C to +200°C
Storage:	12 months in un-opened containers in normal warehouse conditions.
Packaging:	CM STAY WHITE is packed in a recyclable grade plastic cartridge container approximately 310ml.
Colour range:	White

MICROTEC Silver nano antibacterial technology
***a powerful additive which prevents black
mould ,mildew and bacterial growth.***

PREPARATION OF SURFACES

Thorough preparation is essential.

The joint should be completely dry and free from all traces of dirt, dust, grease and any previous sealants or other foreign matter.

All joints should be clean, dry and oil free.

In all cases a clean bonding surface must be obtained.

Following preparation of section joints place into the base of the joint a bond breaker or back up foam to form the correct cross section for the joint sealant bonding to the base of the joint.

CLEANING

After cleaning the joint it should be wiped with CM Multi Wipes care being taken to ensure complete coverage.

Allow Five minutes after wiping for the solvent to evaporate.

It is important for optimum performance of **CM STAY WHITE** that CM Multi Wipes are used

APPLICATION

Cut off top of the cartridge just above nozzle thread

Screw nozzle into place and cut the nozzle to the required size at an angle of 45 degrees.

Apply by gun – place the nozzle angle flush to the joint and extrude a continuous bead of **CM STAY WHITE** into the joint.

Move the nozzle along the joint while extruding.

Adequate contact between **CM STAY WHITE** and the substrate must be ensured to eliminate the possibility of adhesion failure.

After sealing release gun pressure

SURFACE AND EDGE FINISHING

The edges of joints must be kept clean and to a neat line by use of masking tape

This masking will protect the surface adjacent to the joint and should be removed after application of **CM STAY WHITE** and before it has set

NOTE:

Lower temperatures retard cure.

DO NOT APPLY CM STAY WHITE AT TEMPERATURES BELOW 5°C.

Does not cure well in arid conditions.

CLEANING OF TOOLS

Tools should be cleaned after use with CM Multi Wipes

CARE OF PRODUCT

Cured silicone should be cleaned with fresh clean water at least once a week to help maintain its pure white colour.

If silicone is damaged it should be cut away and re-jointed

LIMITATIONS

Do not use as a Aquarium silicone

Not intended as a exterior use

HEALTH AND SAFETY

CM STAY WHITE may cause irritation if swallowed or comes into contact with skin or eyes.

Qualified medical attention should always be sought.

DO NOT INDUCE VOMITING.

Wear suitable gloves and face/eye protection

Do not breathe fumes and keep away from source of ignition.

Products supplied by CM SEALANTS conform to the chemical and physical properties stated in Technical Data Sheets, if they are within their stated shelf life. Any further information or advice both in writing or verbally is given in good faith to assist customers, but as the conditions of use are beyond our control, no warranty is implied or given.

This information must on no account be used as a substitute for necessary prior tests, which alone can determine the suitability for the intended use and assume all risks and liability from the use of the product. The liability of CM SEALANTS will not exceed the original purchase price of the product.

It is in the users responsibility to ensure that they have the latest issue of this document.