



Building & DIY Products You Can Trust

Site 41, Knowsthorpe Way,

Cross Green Industrial Estate, Leeds, LS9 0SW

Telephone: +44 (0) 113 240 3456 Sales: +44 (0) 113 240 2424

Fax: +44 (0) 113 240 0024

e-mail: info@everbuild.co.uk

website: www.everbuild.co.uk

CONSTRUCTION PRODUCTS REGULATION

DECLARATION OF PERFORMANCE

No: INDPU25/1-CPR/ 2013

1. Identification Code	Puraflex 25 Codes: INDPU25 BK/BN/BU/GY/WE
2. Type, Batch and/or Serial Number	Batch number - see packaging label
3. Intended use	Sealant for façade for interior and exterior application (intended for use in cold climates)
4. Manufacturer	Everbuild Building Products Ltd, Site 41, Cross Green Industrial Estate, Knowsthorpe Way, Leeds, LS9 0SW
5. Authorised Representative	Not Applicable
6. Assessment and Verification of Constancy of Performance	System 3 for the type testing System 3 for the reaction to fire testing
7. Notified Body and Tasks	The notified body SKZ Tecona GmbH, identification number 1213, performed the type testing and the testing of reaction to fire and issued test report and classification
8. European Technical Assessment	Not Applicable



Building & DIY Products You Can Trust

Site 41, Knowsthorpe Way,
 Cross Green Industrial Estate, Leeds, LS9 0SW
 Telephone: +44 (0) 113 240 3456 Sales: +44 (0) 113 240 2424
 Fax: +44 (0) 113 240 0024
 e-mail: info@everbuild.co.uk
 website: www.everbuild.co.uk

9. Declaration of performance

Conditioning: Method B

Substrate: Mortar M1, Sika Primer-3 N

Essential Characteristics	Performance	Test Standard	Harmonised technical specification
Reaction to fire	Class E	EN ISO 13238 Classification acc. EN 13501-1:2010	EN 15651-1:2012
Release of chemicals dangerous to the environment and health	NPD	EN 15651-1:2012; 4.5	
Water tightness and air tightness			
Resistance to flow	= 3 mm	EN ISO 7390	
Loss of volume	= 10 %	EN ISO 10563	
Tensile properties at maintained extension after water immersion (elastic)	NF	EN ISO 10590	
Tensile properties for non-structural sealants used in joints in cold climate areas (-30°C)	NF	EN ISO 8340 modified	
Durability	pass	EN ISO 8340 EN ISO 9047 EN ISO 10590	

1213

1003, 1009



13

EN 15651-1:2012

Sealant for façade for interior and exterior applications (intended for use in cold climates)
 F EXT-INT CC

Conditioning: Method B
 Substrate: Mortar M1, Sika Primer-3 N

Essential Characteristics	Performance
Reaction to fire	Class E
Release of chemicals dangerous to the environment and health	NPD
Water tightness and air tightness EN 15651-1:2012	
Resistance to flow	= 3 mm
Loss of volume	= 10 %
Tensile properties at maintained extension after water immersion (elastic)	NF
	NF



Building & DIY Products You Can Trust

Site 41, Knowsthorpe Way,
Cross Green Industrial Estate, Leeds, LS9 0SW
Telephone: +44 (0) 113 240 3456 Sales: +44 (0) 113 240 2424
Fax: +44 (0) 113 240 0024
e-mail: info@everbuild.co.uk
website: www.everbuild.co.uk

Tensile properties for non-structural sealants used
in joints in cold climate areas (-30°C)

Durability

pass

10. Declaration

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9 . The declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed: I. G. Southerington – Head of Technical

A handwritten signature in blue ink, appearing to read 'I. G. Southerington', with a long horizontal stroke extending to the right.

Dated: Leeds, 11/11/2013