

DECLARATION OF PERFORMANCE N. CPR- GB1/0071

- 1) Unique identification code of the product-type: **KERAQUICK S1 WHITE**
- 2) Intended uses: **Improved, fast setting, cementitious adhesive for internal and external tiling on floors and walls**
- 3) Manufacturer: **MAPEI U.K. Ltd, Mapei House, Steel Park Road, Halesowen, West Midlands B62 8HD**

www.mapei.co.uk

- 4) Systems of AVCP: **System 3**
System 4 (for reaction to fire)

- 5) Harmonized standards: **EN 12004:2007+A1:2012**

Notified bodies: **The notified testing laboratory TUM München N. 1211 carried out the assessment of the performance (other than reaction to fire) on the basis of testing on samples taken by the manufacturer.**

- 6) Performances declared:

Essential characteristics	Performances
Reaction to fire	Class E
Bond strength, as:	
- Initial tensile adhesion strength	$\geq 1,0 \text{ N/mm}^2$
- Early tensile adhesion strength	$\geq 0,5 \text{ N/mm}^2$
Durability for:	
- Tensile adhesion after heat ageing	$\geq 1,0 \text{ N/mm}^2$
- Tensile adhesion after water immersion	$\geq 1,0 \text{ N/mm}^2$
- Tensile adhesion after freeze/thaw cycles	$\geq 1,0 \text{ N/mm}^2$
Release of dangerous substances	see SDS

The performance of the product identified above is in conformity with the set of declared performances.

This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: **Peter Dube – Quality Manager**

Halesowen, 07/04/2015





DoP in Pdf format are available in the Mapei website.

<i>Revision 0 notes:</i>	<i>First issue</i>
--------------------------	--------------------

KERAQUICK S1 WHITE
CE MARKING
Annex to DoP N. CPR-GB1/0071



 1211	 MAPEI U.K. Ltd, Mapei House, Steel Park Road, Halesowen, West Midlands B62 8HD www.mapei.co.uk
15 CPR- GB1/0071 EN 12004:2007+A1:2012 KERAQUICK S1 WHITE <i>Improved, fast setting, cementitious adhesive for internal and external tiling on floors and walls</i>	
Reaction to fire Bond strength, as: - Initial tensile adhesion strength - Early tensile adhesion strength Durability for: Tensile adhesion after heat ageing - Tensile adhesion after water immersion - Tensile adhesion after freeze/thaw cycles Release of dangerous substances	Class E $\geq 1,0 \text{ N/mm}^2$ $\geq 0,5 \text{ N/mm}^2$ $\geq 1,0 \text{ N/mm}^2$ $\geq 1,0 \text{ N/mm}^2$ $\geq 1,0 \text{ N/mm}^2$ see SDS

Note:

MAPEI supplies the current annex along with the DoP to make the consultancy of the CE marking easier for the international clients. The enclosed CE marking can be slightly different compared to the one printed on the relevant packaging or documentation because of:

- graphic adaptations due to lack of space on the packaging or printing methods used,
- different language (the same packaging can be shared by several countries),
- the product is already in stock when the updating of the CE marking is implemented,
- printing mistakes.